


MODELS RF10/20 / TINY / RF30

Proximity Card Readers



RF10



RF20



RF-TINY



RF30

Features:

- 125KHz Proximity Card Reader
- Read Range: RF10 / 20 / TINY-Up to 4 inch
RF30 - Up to 12 inch
- 26bit Wiegand (default) / RS232 and ABA Track II (optional) Output Format
- Dual Reading Technology (Active and Passive Cards)
- Easy to install on Metal Door Frame or Mullion
- External LED Control
- External Buzzer Control
- Indoor / Outdoor Operation
- Solid Epoxy Potted
- Waterproof / IP65 / IP66
- Warranty: Life Time
- Reverse Polarity Protection
- Options: Supervisory Signal
- Read Range: up to 12 inch

Proximity Card & Key Tag

- ISO Credit Card Size and Thickness (IDC80)
- 125KHz / Passive Type
- Combination available with Magnetic Stripe (IDC80)
- Printing Company Logo with Graphic (IDC80 Front & Rear)
- Key Tag (IDK50 / L XK50) & Key Holder (L XK50)
- MiniProx Sticker Tag (IMC125)
- Easy to attach on Personal Belongings using IMC125 (MS / Barcode Card, Wallet, PDA, Cell Phone)



ENGINEERED PARKING SYSTEMS

25010 AVENUE TIBBITTS, VALENCIA, CA 91355
PHONE (661) 294-0778 (800) EPSINFO (377-4636) FAX (661) 294-0674
www.epsinfo.com